


# SPIE Web

The website for optics, photonics, and imaging

## PUBLICATIONS



SPIE HOME	<b>PUBLICATIONS</b>	CONFERENCES	EXHIBITIONS	MEMBERSHIP	EDUCATION
SPIE BOOKSTORE	JOURNALS	PROCEEDINGS	SPIE PRESS	MAGAZINES	AUTHOR INFORMATION
				ADVANCED SEARCH	

SEARCH PUBLICATIONS »  
USING IKCITE®
☐ Volumes  
☒ Papers


view cart

### BROWSE PUBLICATIONS

- [Aerospace, Remote Sensing, & Astronomy](#)
- [Automation, Inspection, & Product Engineering](#)
- [Biomedical Optics](#)
- [Communications & Fiber Optics](#)
- [Electronic Imaging, Displays, & Medical Imaging](#)
- [Lasers & Applications](#)
- [Microelectronics, Optoelectronics, & Micromachining](#)
- [Optical Physics, Chemistry, & Biology](#)
- [Optical Science & Engineering](#)
- [Signal & Image Processing](#)

## Abstract

### PUBLICATIONS

### Three-dimensional display system for medical imaging with computer-generated integral photography

Nakajima, Susumu, Masamune, Ken, Sakuma, Ichiro, Dohi, Takeyoshi, Univ. of Tokyo

**Publication:** *Proc. SPIE Vol. 3957, p. 60-67, Stereoscopic Displays and Virtual Reality Systems VII, John O. Merritt; Stephen A. Benton; Andrew J. Woods; Mark T. Bolas; Eds.***Publication Date:** 5/2000

#### Abstract:

A 3D display system for medical image by computer-generated integral photography (IP) has been developed. A new, fast, 3D-rendering algorithm has been devised to overcome the difficulties that have prevented practical application of computer-generated IP, namely, the cost of computation, and the pseudoscopic image problem. The display system as developed requires only a personal computer, a liquid crystal display (LCD), and a fly's eye lens (FEL). Each point in 3D space is reconstructed by the convergence of rays from many pixels on the LCD through the FEL. As the number of such points is limited by the low resolution of the LCD, the algorithm computes a coordinate of the best point for each pixel of the LCD. This reduces computation, performs hidden surface removal and solves the pseudoscopic image problem. In tests of the system, the locations of images projected 10-40 mm distant from the display were found to be less than 2.5 mm in error. Both stationary and moving IP images of a colored skull, generated from 3D computerized tomography, were projected and could be observed with motion parallax within 10 degrees, both horizontally and vertically, from the front of the display. It can be concluded that the simplicity of design and the geometrical accuracy of projection give this system significant advantages over other 3D display methods.

©2003 SPIE--The International Society for Optical Engineering. Downloading of the abstract is permitted for personal use only.

You may order this paper or volume online

[Order this paper](#)[Order this volume](#)Use your browser's **Back** button to return to the search results
[| SPIE Home](#) | [Publications](#) | [Conferences](#) | [Exhibitions](#) | [Membership](#) | [Education](#) |
Telephone: +1 360/676-3290 | Fax +1 360/647-1445 | Email: [spie@spie.org](mailto:spie@spie.org)

© 1994-2002 SPIE--The International Society for Optical Engineering

Order